

RGPC 600 RM Pro

Parallel Power Delivery for
Load Impedance matching

New and Improved! Parallel Power Delivery

The RGPC 600 RM Pro is designed for installations where the ratio of space/performance is at premium. Its Parallel Delivery Choke Technology is specifically designed to fit into a 2U rack space, With three duplex outlets on the back and a convenience outlet on the front, its is capable to power most midsized home theater systems.

To receive the maximum performances install the RGPC 600 RM Pro as close as possible to the AV equipment.

The RGPC 600 RM Pro, utilizes Balanced Surge Protection Design (SPD) to ensure Bidirectional Protection and Reduced Ground Interference.

Applications

- All AV equipment
- Midsized Home Theaters
- Installations with Multiple Circuits
- For Crisp and Flawless AV Experience

Features & Benefits

- High Current on Demand
- 2 Individually triggered Duplex Outlets
- 1 RGPC 75 Ohm Coax Surge Protector
- Balanced AC Surge Protection
- Resettable Circuit Breaker
- Compatible with UL1449 3rd edition for Type 3 locations



Specifications

Dimensions (WHD)

Net weight

Rack Mountable

Power Cord Low Impedance (Detachable)

Outlets

Sequentially Turned On Outlets w/12V triggers

Input Voltage

Output Voltage

Frequency

Output Power

Technology

RGPC 75 ohm Coax Protector, 180V, 500A, <1Ω

AC Surge Protection (type 3 locations)

Efficiency

Cooling

Storage Temperature

Operating Temperature

600 RM Pro 120/120

17 x 3.5 x 11

32 lbs

Yes, rack ears included

6 ft, 12 AWG, NEMA 5-15P

6 NEMA 5-20R,

1 NEMA 5-20R on front

2 Duplex Switched, 1 Duplex NS

120 VAC

120 VAC

60 HZ

12 A (1,440 Watts)

Parallel Delivery

1 Port (In-Out)

Balanced

>99%

Convectional

-40° C to 85° C

-40° C to 65° C

600 RM Pro 240/240

17 x 3.5 x 11

32 lbs

Yes, rack ears included

6 ft, 12 AWG, Euro Schuko Plug

4 Euro Shuko

NA

240 VAC

240 VAC

50 HZ

12 A (2,880 Watts)

Parallel Delivery

1 Port (In-Out)

Balanced

>99%

Convectional

-40° C to 85° C

-40° C to 65° C

