



400 Pro

Parallel Power Delivery

The RGPC 400 Pro retains its original Parallel Power performance, and its compact design fits conveniently behind an equipment rack.

To receive the maximum performance install the RGPC 400 Pro as close as possible to the AV equipment. The RGPC 400 Pro utilizes Balanced Surge Protection Design (SPD) to ensure Bidirectional Protection and Reduced Ground Interference.

FEATURES & BENEFITS

- High current on demand
- Balanced AC surge protection
- Resettable circuit breaker
- Compact design
- Compatible with UL1449 3rd edition for Type 3 locations
- Indicator lights

APPLICATIONS

- All AV equipment
- Smaller systems
- Multiple units on same circuit yield increased performance
- Installations with multiple circuits
- For crisp and flawless AV experience

PARALLEL POWER DELIVERY FOR LOAD IMPEDANCE MATCHING

SPECIFICATIONS	400 PRO 120/120	400 PRO 240/240
Dimensions (WHD)	8.5 x 9 x 6 inches	8.5 x 9 x 6 inches
Net weight	18 lbs	18 lbs
Mounting	Stand alone Floor / Shelf	Stand alone Floor / Shelf
Power Cord (Detachable)	6 ft, 12 AWG, NEMA 5-15P	6 ft, 12 AWG, Euro Schuko Plug
Outlets	4 (NEMA 5-20R)	4 Euro Schuko
Input Voltage	120 VAC	240 VAC
Output Voltage	120 VAC	240 VAC
Frequency	60 HZ	50 HZ
Output Power	12 A (1,440 Watts)	12 A (2,880 Watts)
Technology	Parallel Power Delivery	Parallel Power Delivery
AC Surge Protection (type 3 locations)	Balanced	Balanced
Efficiency	>99%	>99%
Cooling	Convectional	Convectional
Indicator Light	Blue LED	Blue LED
Storage Temperature	-40° C to 85° C	-40° C to 85° C
Operating Temperature	-40° C to 65° C	-40° C to 65° C