



RGPC 600S

Parallel Power Delivery Model

The RGPC 600 S (available in black or silver) with its beautiful award winning Art Deco design, switchable backlit logo (blue, orange or off) is available as a stand alone or rack mounted. With three duplex outlets the 600 S is large enough to power most midsized home theater and two channel systems.

To receive the maximum performances install the RGPC 600S as close as possible to the AV equipment. The RGPC 600 S, utilizes Balanced Surge Protection Design (SPD) to ensure Bidirectional Protection and Reduced Ground Interference.

FEATURES & BENEFITS

- High current on demand
- Balanced AC surge protection
- Resettable circuit breaker
- Rack mountable with optional self kit
- Compatible with UL1449 3rd edition for Type 3 locations
- Orange or Blue Illuminated Front – rear switch

APPLICATIONS

- All AV equipment
- Midsized home theaters
- Installations with multiple circuits
- For crisp and flawless AV experience

**PARALLEL POWER DELIVERY FOR LOAD
IMPEDANCE MATCHING**

| SPECIFICATIONS | 600 S 120/120 | 600 S 240/240 |
|--|-----------------------------|--------------------------------|
| Dimensions (WHD) | 8.75 x 5.25(w/feet 6.2) x11 | 8.75 x 5.25(w/feet 6.2) x11 |
| Net weight | 30 lbs | 30 lbs |
| Mounting | Stand alone Floor / Shelf | Stand alone Floor / Shelf |
| Rack Mountable | w/ mounting kits | w/ mounting kits |
| Power Cord (Detachable) | 6 ft, 12 AWG, NEMA 5-15P | 6 ft, 12 AWG, Euro Schuko Plug |
| Outlets | 6 (NEMA 5-20R) | 4 Euro Schuko |
| Input Voltage | 120 VAC | 240 VAC |
| Output Voltage | 120 VAC | 240 VAC |
| Frequency | 60 HZ | 50 HZ |
| Output Power | 12 A (1,440 Watts) | 12 A (2,880 Watts) |
| Technology | Parallel Power Delivery | Parallel Power Delivery |
| AC Surge Protection (type 3 locations) | Balanced | Balanced |
| Efficiency | >99% | >99% |
| Cooling C | Convectional | Convectional |
| Storage Temperature | -40° C to 85° C | -40° C to 85° C |
| Operating Temperature | -40° C to 65° C | -40° C to 65° C |